

Home ■ Prodotti ■ Grigliatura grossolana, fine e finissima ■ Impianti ROTAMAT® ■
HUBER Rotostaccio ROTAMAT® Ro2 / RPPS / STAR

HUBER Rotostaccio ROTAMAT® Ro2 / RPPS / STAR



Reliable and well-proven inlet screen for municipal sewage treatment plants and industrial wastewater and process water screening

- fine screen with wedge (Ro2) or perforated plate (RPPS) or folded perforated plate (STAR)
- with integrated screenings press and screenings washing
- more than 2,000 installations worldwide

The ROTAMAT® Rotary Drum Fine Screen / Perforated Plate Screen RPPS is completely made of stainless steel and is acid treated in a pickling bath. They are either installed directly into channels or are supplied as tank-mounted units, with an inclination of 35°.

Model variations

■ **Ro2: Wedge wire screen ≥ 0.5 mm**

Depending on the screen bar spacing (0.5 - 6 mm) and screen size (screen basket diameter of up to 3000 mm), the throughput can be individually adjusted to specific site requirements.

■ **RPPS: Perforated plate screen basket ≥ 1,5 mm**

Compared to one-dimensional wedge wire screens, the two-dimensional screening element of the Rotary Drum Fine Screen ROTAMAT® RPPS achieves a significantly higher separation efficiency.

- **STAR: Folded perforated plate screen basket ≥ 1,0 mm**

The star-shaped screen basket with a zigzag folded surface of the Perforated Plate Screen ROTAMAT® STAR provides an increased free screen surface and an approximately 30% increase in throughput capacity with the same nominal diameter. STAR units are preferably used with fine perforations of 1 / 1.5 / 2 mm for installation on municipal and industrial wastewater treatment plants.

- **PRO-Series option**

The special design of the PRO series isolates the water level in the trough from the water levels upstream and downstream of the screen. This operation method permits continuous screen operation with a constant water level upstream of the machine and significantly increases throughput capacity.

Dependant on the bar spacing (0.5 - 6 mm) or plate perforation (1 - 6 mm) and the drum diameter (up to 3000 mm) any flow rate can be realised.

The wastewater flows into and through the open end of the inclined screen basket with the floating and suspended materials being retained by the screen basket. Blinding of the screen surface generates an additional filtering effect so that suspended materials can be retained that are smaller than the bar or perforation of the screen basket. The basket starts to rotate when a certain upstream water level is exceeded due to screen surface blinding.

The rotating screen drum lifts the screenings and drops them into the centrally arranged trough. Screenings removal is supported by a scraper brush and spray bar. A screw conveyor in the trough rotates and transports the screenings through an inclined pipe.

The conveying screw transports, dewateres and compacts the screenings, without odour nuisance, and discharges them into the customer's container or a subsequent conveying unit.

Vantaggi

ADVANTAGES OF THE HUBER ROTAMAT® SCREENS

a) Low headloss – High separation efficiency

Due to the drum's shape and 35° installation the screen area is much larger than that of a vertical or steeply inclined screen, which results in a low headloss, high separation efficiency and maximum throughput.

b) Completely made of stainless steel

The machine is completely made of stainless steel and pickled in an acid bath which eliminates corrosion and thus reduces maintenance.

c) No by-passing

The entire flow enters the screen drum through its open front end and can only leave the drum through its screen area. This prevents plant overflow and guarantees that the screenings are always retained within the screen drum.

d) Several functions combined in one system

The ROTAMAT® Screens perform the functions of screenings removal, transport, washing, dewatering and compaction in a single spacesaving unit. An additional bagging unit guarantees operation of the entire system without odour nuisance.

e) Outdoor installation

For frost-proof outdoor installation, the ROTAMAT® Rotary Drum Fine Screen can be supplied with a heating wire and thermal insulation.

f) Retrofitting

The design of the ROTAMAT® Screens allows for later modification so that the systems can be adapted to changing requirements. The heating and/or integrated screenings washing can be retrofitted. The bar spacing can also be reduced to meet more stringent requirements.

g) Low maintenance

No lubrication. Regular checking and visual inspection are sufficient.

Downloads


 Depliant: ROTAMAT® Rotary Drum Fine Screen Ro 2 / RPPS (inglese) [pdf, 433 KB]

Applicazioni

- Una "STAR" per Star City: Impianto di grigliatura HUBER ROTAMAT® STAR per un impianto di depurazione in Idaho
- Protezione affidabile degli impianti a membrana con impianto di filtraggio HUBER ROTAMAT® STAR liquid

- Further development of the well-proven ROTAMAT® screen concept: new Pro line
- Further developed ROTAMAT® Rotary Drum Fine Screen with increased hydraulic capacity: ROTAMAT® Perforated Plate Screen RPPS-Star
- Mechanical wastewater pre-treatment for membrane bioreactors
- Due nuove griglie a rotostaccio HUBER ROTAMAT® Ro2 2600 XL per l'impianto di depurazione di Salisburgo-Siggerwiesen
- La famiglia HUBER ROTAMAT® – tecnologia collaudata per grandi progetti

Principio di funzionamento



Media





Video: HUBER Rotary Drum Fine Screen ROTAMAT® Ro2 for municipal inlet screening
https://www.youtube.com/watch?v=vyieOQUR_9o



Video: HUBER Rotary Drum Fine Screen ROTAMAT® Ro2 for preliminary wastewater treatment in meat processing industry
<https://www.youtube.com/watch?v=HvwV0BaLd68>



Video: HUBER Rotary Drum Fine Screen ROTAMAT® Ro2 in a grit treatment process for wash-out of organics
<https://www.youtube.com/watch?v=a2fl9eGOEsk>

Altri prodotti della gamma: Impianti ROTAMAT®

- [HUBER Griglia Fine ROTAMAT® Ro1](#)
- [HUBER Filtrococlea ROTAMAT® Ro9](#)
- [HUBER Impianto compatto ROTAMAT® Ro5](#)
- [HUBER Impianto compatto Hydro-Duct ROTAMAT® Ro5 HD](#)
- [HUBER Coanda Impianto compatto ROTAMAT® Ro5 C](#)
- [HUBER Membrane Screen ROTAMAT® RoMem®](#)
- [HUBER Griglia protezione pompe ROTAMAT® RoK4](#)

HUBER Technology srl
 P.IVA e C.F. 01689490215
 Cap. Soc. Euro 600.000,00 int. ver.
 Iscr. al Registro delle Imprese
 di Bolzano n. 01689490215

Sede amministrativa:
 Zona Produttiva Vurza, 22
39055 Pineta di Laives (BZ)
 Tel. 0471.590107
 Fax 0471.594280

Sede commerciale:
 Via A. Meucci, 35
27055 Rivanazzano (PV)
 Tel. 0383.934023
 Fax 0383.944453

Internet:
www.huber.de
www.hubertec.it
info@hubertec.it

