

[Home](#) ■ [Prodotti](#) ■ [Trattamento del grigliato](#)

HUBER Pressa con lavaggio del grigliato WAP® SL HP



Lavaggio ottimale e compattazione in un'unica macchina

- Lavaggio grigliato ad alta pressione con zona di lavaggio intensivo e cono a regolazione automatica
- Resa disidratazione fino al 60 % SS
- Riduzioni di peso fino all' 85 %
- Aumento del valore termico del materiale separato

High washout factor due to intensive washing

The HUBER Screenings Wash Press WAP® SL HP operates in a batch mode. Screenings either drop into the launder tank directly from a screen or conveyor, or they are flushed into the tank through a launder channel. After a batch of screenings has been fed, the tank is filled up with wash water and agitated for an adjustable period by means of an impeller.

The faecal matter is loosened and removed from the screenings by high turbulence and shear. The washing intensity is selectable and can be adjusted to suit the specific screenings quality. After the washing cycle has been finished, an automatic valve opens and the wash water drains through perforations in the trough. It returns, together with the faecal matter, to the wastewater flow.

Reduced disposal costs with high pressure

The washed screenings are further conveyed into the press zone where they are dewatered by means of a sturdy compacting screw. In the following automatically controlled second press zone the screenings are constantly compacted and dewatered under high pressure

to a DS content of up to 60 %.

Especially wear-resistant and solid materials in the conical high-pressure unit ensure reliable long-term operation of the plant. The press water from the screenings compaction is collected under the highpressure unit and discharged along with the wash water which is rich in carbon. Automatic cleaning with water of the press and wash water collecting tank under the machine and the complete highpressure unit is possible.

The washed and compacted screenings are finally transported through the conical discharge pipe into a skip.

Vantaggi

THE ADVANTAGES OF THE HUBER SCREENINGS WASH PRESS WAP® SL HP

- High-intensity washing in launder tank
- Dewatering performance of up to 80 % DR
- Volume, weight and disposal cost reduction of up to 85 %
- Hydraulically controlled high-pressure zone
- Return of carbon-rich filtrate to the wastewater
- Screened wastewater or process water can be used as wash water
- Insensitive to coarse material
- Completely made of stainless steel (including the compacting screw)
- Compacting screw with reinforced flights for wear protection
- High economic efficiency due to reduced transport and disposal costs

Downloads

 [Depliant: HUBER Screenings Wash Press WAP/SL/HP \(inglese\)](#) [pdf, 241 KB]

Altri prodotti della gamma: Trattamento del grigliato

- [Pressa con lavaggio del grigliato WAP®](#)
- [Pressa con lavaggio del grigliato WAP/SL](#)
- [Screenings Wash Press WAP® L for Launder Channel Feeding](#)
- [HUBER Launder Channel HLC](#)
- [HUBER Coclea di trasporto](#)
- [HUBER Screenings Compactor Ro7](#)
- [Lavaggio integrato nella griglia](#)

HUBER Technology srl
P.IVA e C.F. 01689490215
Cap. Soc. Euro 600.000,00 int. ver.
Iscr. al Registro delle Imprese
di Bolzano n. 01689490215

Sede amministrativa:
Zona Produttiva Vurza, 22
39055 Pineta di Laives (BZ)
Tel. 0471.590107
Fax 0471.594280

Sede commerciale:
Via A. Meucci, 35
27055 Rivanazzano (PV)
Tel. 0383.934023
Fax 0383.944453

Internet:
www.huber.de
www.hubertec.it
info@hubertec.it

